

```

define ROOT C:\Program Files\nxlog
Moduledir %ROOT%\modules
CacheDir %ROOT%\data
Pidfile %ROOT%\data\nxlog.pid
SpoolDir %ROOT%\data
LogFile %ROOT%\data\nxlog.log
LogLevel INFO

<Extension logrotate>
  Module xm_fileop
  <Schedule>
    When @daily
    Exec file_cycle('%ROOT%\data\nxlog.log', 7);
  </Schedule>
</Extension>

<Extension gelfExt>
  Module xm_gelf
  # Avoid truncation of the short_message field to 64 characters.
  ShortMessageLength 65536
</Extension>

<Input eventlog>
  Module im_msvistalog
  PollInterval 1
  SavePos True
  ReadFromLast True

  #Channel System
  #<QueryXML>
  # <QueryList>
  # <Query Id='1'>
  # <Select Path='Security'*[System/Level=4]</Select>
  # </Query>
  # </QueryList>
  #</QueryXML>
</Input>

<Input file>
  Module im_file
  File 'C:\Windows\MyLogDir\*.log'
  PollInterval 1
  SavePos True
  ReadFromLast True
  Recursive False
  RenameCheck False
  Exec $FileName = file_name(); # Send file name with each message
</Input>

<Output gelf>
  Module om_tcp

```

```
Host 192.168.14.110
Port 16756
OutputType GELF_TCP
#<Exec>
# # These fields are needed for Graylog
# $gl2_source_collector = '${sidecar.nodeId}';
# $collector_node_id = '${sidecar.nodeName}';
#</Exec>
```

</Output>

```
<Route route-1>
  Path eventlog => gelf
</Route>
<Route route-2>
  Path file => gelf
</Route>
```